Zephyr[®] Xtra Quick Start

Unpacking Your Zephyr Xtra

Unpack your box and locate the DCS51 Command Station and the PS314 power supply.

DOIN

DCS 51




Power Cord

DC Plug

6

PS314

Before proceeding to the next step, make sure the Throttle Knob is turned all the way to "STOP" and the Direction/ Brake lever is set to "BRAKE."



Direction/Brake lever in "BRAKE" position



Screw terminal strip

Select and Run DCC **Equipped Locomotives**

Most new decoders and DCC-equipped locomotives have their decoder address factory set to "03." Other DCC-equipped locomotives may have had their address changed. To run a DCC-equipped loco, you must know its address. For detailed instructions on reading the address, see the Zephyr Xtra Manual, Section 16.2 Steps 1-4. LOCO key

For now, let's assume you are using a brand-new, DCCequipped loco that is set to address "03." To select this locomotive, press the key labeled "LOCO" ONCE, enter "O3" on the keypad, and press "LOCO" once again. You have selected a DCC loco!

To run the locomotive, move the Direction/Brake lever to either 'FORWARD" or "REVERSE", depending on which way you want the loco to move, and slowly turn the **Throttle** clockwise until the locomotive starts to move. To stop the loco, either turn the Throttle back to "STOP." or shift the Direction/Brake lever to "BRAKE."

Dispatching a Locomotive

After you are finished running a locomotive, turn the Throttle knob (counter clockwise) to "STOP," press "LOCO" and then "EXIT" to free the locomotive address for use next time.

Connecting the Pieces Together

On the back of the **DCS51**, locate the gray screw terminal strip. On this strip, locate the two terminals labeled "RAIL A" and "RAIL B". Attach your layout track wires to these terminals. It does not matter which is which. Find the jack on the back of the DCS51 marked "POWER IN, 13.8 V DC, 3.5 AMPS" Plug the PS314 DC plug into this jack and then connect the **PS314** into an AC outlet that matches the power cord on the PS314. The PS314 will work universally on 110 through 240V AC.



Keypad





Digitrax, Inc. 2443 Transmitter Road Panama City, FL 32404 Phone (850) 872-9890 Fax (850) 872-9557 www.digitrax.com

Select and Run Non-DCC Locomotives

Cable Tester

To select a non-DCC equipped (Analog) locomotive to run, look at the main group of keys on the front panel. Locate the one labeled "LOCO". Press this key ONCE, enter "OO" and press "LOCO" once again. You have selected a locomotive to run!


LT1 Decoder and LocoNet[®]

To run the locomotive, place the locomotive on your layout, move the Direction/Brake lever to either 'FORWARD" or "REVERSE", depending on which way you want the locomotive to move, and slowly turn the Throttle clockwise until the locomotive starts to move. If your locomotive runs in the opposite direction of the throttle setting, turn the locomotive around. To stop the locomotive, either turn the Throttle back to "STOP," or shift the Direction/Brake lever to "BRAKE". Keypad

LOCO key

DCS51

Command Station



Direction/Brake lever in "FORWARD" position

Turn on Track Power

On the front panel of the DCS51, locate the key marked "POWER." It is on the left hand column of keys. When you push it, the orange "TRACK STATUS" light will come on.

Track Status Light **POWER** key PS314 DCS 51

What's Next?

If you've been able to successfully run your DC or DCC equipped locomotive using these instructions, then we recommend you visit us at digitrax.com and read more about DCC principles, accessories and web links of interest. The spiral-bound Zephyr Xtra Manual included in your starter set will provide you with a wealth of knowledge which will increase your enjoyment of DCC!

If you've been unable to run your locomotive, please carefully re-read this Quick Start Guide, making sure you've correctly followed the instructions. If you are still unable to run your loco, Digitrax live tech support is available Monday through Friday 8:30AM-4:45PM CST at (850) 872-9890. Tech support questions can also be submitted by e-mail to:

> techsupport@digitrax.com or by fax to (850) 872-9557

24/7 help is available at the Tech Support Depot - go to www.digitrax.com/help and try it out!

Thank you for choosing Digitrax - we're glad you're part of the World's Greatest Hobby[®]. Whether you are a beginner or have been in the hobby for many years, Digitrax will be here to help you every step of the way!!